



## LCR METER

**6375/6376/6377**

### Key Features

- 0.1% Basic Accuracy
- Up to 1MHz Frequency
- 5 Digits Frequency Step Resolution
- Comprehensive Measurement Functions
- Straight Forward Intuitive Operation
- GPIB and RS-232 Interface
- Unbeatable Performance
- Unbeatable Price

### • Comprehensive measurement functions

Providing all the well-known measurement parameters :

Impedance | Z | 、Admittance | Y | 、Phase Angle (  $\theta$  ) 、Reactance (X) 、Conductance (G) 、Susceptance (B) 、Inductance (L) 、Capacitance (C) 、Quality Factor (Q) 、Dissipation Factor (D) 、Resistance (DCR)

### • Continuous frequency range from 20Hz to 1MHz

Providing a continuous variable frequency from 20Hz to 1MHz, 5 digits resolution, testing all components at the desired test frequency, allowing a component to be test at a actual operating frequency.

### • Multi step

Tuning voltage, frequency, and testing parameters arbitrarily, making complicated testing become easier.

### • Fast ! Accurate ! Stable !

Testing components is easy with 6375 Series LCR Meter. Just connect the component and the meter accurately measures the component, displaying selected primary and secondary value with a basic accuracy of 0.1%.

### • Flexible! Full remote control!

Providing control and output capability, the 6375 Series offers useful interface such as GPIB, RS232 and handler port, making remote control straightforward.

## ● 6375/6376/6377 LCR METER

Measurement Item		
MEasurement parameters		
Z   ,   Y   , $\theta$ , R, X, G, B, L, C, Q, D, ESR, DCR measurement Circuit : Series/Parallel		
Mathematical Functions		
absolute/percent deviation		
Test Signal Information		
Test Frequency		
6375	20Hz ~ 200kHz	
6376	20Hz ~ 500kHz	
6377	20Hz ~ 1MHz	
Frequency Step Resolution	5 Digits	
Frequency Accuracy	$\pm 0.01\%$	
Output Impedance	100 $\Omega$	
AC Drive Level	10mV 至 2Vrms (1mVrms steps)	
Measurement Range		
Z   R X	0.1m $\Omega$ ~ 100M $\Omega$	
y   G B	10nS ~ 1000S	
C	0.01pF ~ >1F	
L	0.01nH ~ 100KH	
D	0.00001 ~ 9.9999	
Q	0.1 ~ 9999.9	
$\theta$	-180° ~ +180°	
DCR	0.1m $\Omega$ ~ 100M $\Omega$	
$\Delta\%$	-999.99% ~ 999.99%	
Basic Accuracy		
$\pm 0.1\%$   Z   , R, X,   Y   , G, B, C, L		
Measurement Time		
	DC	AC
Max :	30 ms	75 ms
Fast :	60 ms	150 ms
Medium :	120 ms	450 ms
Slow :	500 ms	600 ms

LCD Display	
320x240 Graphic Display	
Correction	
Zero OPEN / SHORT : Eliminates measurement error due to stray parasitic impedances in the test fixtures	
Comparator Function	
High/Pass/Low For each primary measurement parameter and secondary measurement parameter	
Other Functions	
Save/Recall	
64 Multi-step files can be saved/recalled from the internal nonvolatile memory	
Continuous Memory Capability	
If the instrument is turned off, or if a power failure occurs, instrument setting are automatically memorized	
Interface	
RS-232, GPIB, Handler (option)	
General Specifications	
Power Requirement	
Input Voltage	90~132Vac or 198~264Vac(selectable)
Frequency	47~66Hz
Test Environment	
Operation Temperature	10°C to 40°C
Operation Humidity	<95% at 40°C
Size and Weight	
Height	150 mm
Width	340 mm
Depth	460 mm
Weight	6.5 Kg

Specifications are subject to change without any prior notice!! All products and company named used herein are for identification only. All (registered) trademarks are alright of their respective owners.